

締付けトルク値参考資料(概算)

単位(N・m)

適用区分 ボルト呼び	鋼製ボルト				
	強度区分	強度区分	強度区分	強度区分	強度区分
	4.6	6.8	8.8	10.9	12.9
M 2	0.12	0.238	0.319	0.447	0.536
M 2.5	0.245	0.487	0.650	0.915	1.10
M 3	0.434	0.870	1.16	1.63	1.96
M 3.5	0.683	1.37	1.82	2.56	3.08
M 4	1.01	2.02	2.70	3.79	4.54
M 5	2.04	4.09	5.47	7.67	9.18
M 6	3.47	6.97	9.27	13.0	15.6
M 7	5.85	11.6	15.5	21.8	26.2
M 8	8.41	16.9	22.5	31.6	37.9
M10	16.7	33.4	44.5	62.6	75.2
M12	29.1	58.3	77.6	109	131
M14	46.4	92.7	124	174	209
M16	72.3	145	194	271	325
M18	100	199	266	373	447
M20	141	282	376	529	635
M22	192	384	511	720	865
M24	244	488	650	915	1,100
M27	358	713	951	1,340	1,610
M30	484	971	1,290	1,820	2,180
M33	661	1,320	1,760	2,470	2,970
M36	848	1,690	2,260	3,180	3,810
M39	1,100	2,190	2,920	4,110	4,930
M42	1,350	2,710	3,610	5,080	6,080
M45	1,700	3,400	4,540	6,370	7,630
M48	2,030	4,060	5,440	7,620	9,120
M52	2,640	5,290	7,040	9,880	11,800
M56	3,270	6,560	8,710	12,300	14,800
M60	4,080	8,180	10,900	15,300	18,300
M64	4,930	9,890	13,100	18,500	22,300
M68	5,970	12,000	16,000	22,500	27,000
M72	7,150	14,400	19,100	26,900	32,300
M76	8,540	17,000	22,700	31,900	38,300
M80	10,000	20,000	26,600	37,500	45,000

注)トルク値は使用条件により異なりますのでトルクレンチご購入時の参考値としてのみご利用ください。
(トルク係数0.2、最大軸力をボルト耐力の80%として算出、ボルトはJIS強度区分による。)